





TTS 2255

TTS 2265



✓
KIT ACCELERATORE A RICHIESTA
SELF THROTTLE KIT UNDER REQUEST

			
Type	n.	n.	n.
TTS 2255/450	2	4	0-1
TTS 2265/520	2	5	1













Motocompressore

Motocompressore ad alte prestazioni con motore a scoppio a benzina 4 tempi. Avviamento a strappo con fune autoavvolgente. Testata bicilindrica monostadio con cilindro in ghisa ad elevato rendimento d'aria. Valvola automatica di sfiato e messa a vuoto che mantiene la pressione costante nel serbatoio. Completo di filtro-riduttore-lubrificatore e ripartitore con attacchi multipli. Un telaio pratico e maneggevole dotato di ruote pneumatiche lo rende adatto per l'utilizzo in agricoltura.

Petrol engine air compressors

High-performance motor compressor with 4-stroke petrol engine. Self rewinding rope starter. Single-stage two-cylinders compressor heads with cast iron cylinder at high performance air delivery. Automatic release valve and vacuum setting which maintains a constant pressure in the tank. Complete with filter-reducer-lubricator and distribution manifold.

Provided with pneumatic wheels and handly frame, suitable for agricultural use.

																	
Type	Lt.	Type	L/min.	m ³ /h	c.f.m.	HP	r.p.m.	n.	Stage n.	bar	p.s.i.	kg	L	B	H	LpA (R-Tr-H-Tm)	LwA
TTS 2255/450	11+11	K17/C	450	27,1	15,5	5,5	1300	2	1	11	160	65	880	690	880	≤ 95	97
TTS 2265/520	11+11	K18/C	520	31,2	18,36	6,5	1300	2	1	11	160	68	880	690	880	≤ 95	97